



Pilkington Activ™ Blue Self-cleaning Solar Control Glass

Pilkington Activ™



self-cleaning glass

The attractive blue glass that combines dual-action, self-cleaning properties with solar control performance for a cooler internal environment.

Specially designed for conservatories, conservatory roof replacements and large glazed areas, Pilkington Activ™ Blue is a revolutionary new glass that is perfect for use in both the roof and verticals. It uses daylight and rainwater to break down and wash away organic dirt from exterior surfaces, making it ideal for hard to reach places that are difficult to clean. Its unique blue colour also helps keep internal temperatures cooler whilst still maintaining excellent light transmittance. For optimum self-cleaning and thermal performance, combine Pilkington Activ™ Blue with Pilkington K Glass™ in an Insulating Glass Unit.



PILKINGTON
NSG Group Flat Glass Business

Pilkington Activ™ Blue

	Light		Solar Radiant Heat				Shading Coefficient			U value (W/m²k)	
	Transmittance	Reflectance	Direct Transmittance	Reflectance	Absorptance	Total Transmittance	Short wave-length	Long wave-length	Total		
Single Glazing Performance											
4 mm	0.59	0.15	0.44	0.13	0.43	0.55	0.51	0.12	0.63	5.8	
6 mm	0.49	0.14	0.33	0.12	0.55	0.47	0.38	0.16	0.54	5.7	
10 mm	0.35	0.13	0.21	0.12	0.67	0.38	0.24	0.20	0.44	5.6	
Insulating Glass Unit Performance – (4 mm Pilkington Activ™ Blue outer pane and 16 mm cavity)										Air	Argon*
4 mm Pilkington Optifloat™ inner pane	0.53	0.18	0.38	0.15	0.47	0.45	0.44	0.08	0.52	2.7	2.6
4 mm Pilkington K Glass™ inner pane	0.49	0.19	0.33	0.16	0.51	0.41	0.38	0.09	0.47	1.7	1.5
4 mm Pilkington Optitherm™ S4 inner pane	0.51	0.17	0.31	0.17	0.52	0.38	0.36	0.08	0.44	1.4	1.2

*90% Argon gas fill. Figures based on EN 410 (90% Argon gas fill) and EN 673.



Pilkington Activ™ Blue must always be processed, installed and maintained in accordance with our specialist Handling and Processing instructions for Pilkington Activ™.

Benefits

- Attractive blue colour offers excellent aesthetics and optimum performance
 - Excellent solar control performance combined with good light transmission
 - Uses daylight and rainwater to break down and wash away organic dirt from the exterior of the glass
 - Works even on cloudy days and during the night
 - Pilkington Activ™ coating lasts the lifetime of the glass
 - Easily cleaned during dry spells by hosing down
 - Low exterior reflection improves aesthetics of the conservatory
 - Easily stocked and fabricated into Insulating Glass Units in annealed and toughened forms, ensuring speedy delivery
 - Available in 4 mm, 6 mm and 10 mm thicknesses
 - Can be combined with Low-E glass (Pilkington K Glass™, or Pilkington Optitherm™ S4) and argon gas for the ultimate conservatory roof unit
- Please visit www.pilkington.co.uk/selfcleaningglass for more information

To the fullest extent permitted by applicable laws, Nippon Sheet Glass Co. Ltd. and its subsidiary companies disclaim all liability for any error in or omission from this publication and for all consequences of relying on it.

Due to print limitations imagery is for illustration purposes only. For exact colouration, please request a sample.



CE marking confirms that a product complies with its relevant harmonised European Norm. The CE marking label for each product, including declared values, can be found at www.pilkington.com/CE



PILKINGTON
NSG Group Flat Glass Business

Building Products - UK
Prescot Road St Helens WA10 3TT United Kingdom
Telephone 01744 692000 Fax 01744 692880
pilkington@respond.uk.com
www.pilkington.co.uk